



Type	Displacement cm <sup>3</sup> /rev	Flow		Pressure P <sub>nom</sub> bar	max Speed n rpm	Dimension							
		at 1500 rpm V <sub>min</sub>	at max rpm V <sub>min</sub>			A mm	B mm	Inlet			Outlet		
								E	d	F	E	d	F
ZRP-X32-22	20	28,2	56,4	250	3000	56,1	116,7	40	M8	19			
ZRP-X32-26	22,5	31,7	63,5	250	3000	57,6	119,7						
	25	35,3	70,5	250	3000	58,3	121,1						
	28	39,5	79,0	250	3000	60,2	124,7						
ZRP-X32-31	32	45,1	75,2	250	2500	62,0	128,3	51	M10	27	40	M8	19
	32	45,1	90,2	250	3000	66,5	137,3						
	36	50,8	84,6	250	2500	63,5	131,4						
ZRP-X32-36	36	51,3	95,8	250	2800	68,0	140,5	51	M10	27	40	M8	19
	42	59,9	91,8	230	2300	66,3	137,0						
ZRP-X32-41	42	59,9	99,8	230	2500	70,8	146,1						
ZRP-X32-47	46	65,6	100,5	230	2300	72,7	149,8						
ZRP-X32-51	50	71,3	99,8	200	2100	74,5	153,4	51	M10	27	40	M8	19
	55	78,4	91,4	200	1750	76,7	157,9						
ZRP-X32-61	60	85,5	99,8	180	1750	78,7	162,4						